

KWC zoe



## Art in Motion

Sculptural, innovative and in a class of its own: KWC ZOE brings together all of KWC's kitchen expertise in a single faucet. The result of this successful synthesis of functional variety, organic design and a fascinating interplay of water and light is a unique, unparalleled masterpiece. From every angle, KWC ZOE reveals new aspects of its distinctive character and demonstrates what it is that makes it such a groundbreaking style icon in the world of faucet design.





German  
Design Award

SPECIAL  
MENTION

DESIGN **PLUS**

PRODUCT INNOVATION  
AWARD WINNER

**PIA'13**

### Pull-out spray

The spray, which is integrated flush in the spout, can be pulled out by up to 50 cm. High-quality metallic casing extends the service life of the pull-out hose.



### Two types of jet

It is easy to switch between Neoperl® jet and needle spray at the touch of a button.



### Turn And Clean and JETCLEAN

Easy cleaning of the spray (Turn And Clean) and effective protection against limescale (JETCLEAN), all in one.



### LED light

The LUMINAQUA® LED function light can be operated using an ON/OFF membrane button integrated in the pull-out spray. It switches off automatically after 30 minutes.

#### LED: long-lasting and economical

Long lifespan, ultra-low energy consumption – LEDs consume around five times less energy than conventional light bulbs.



### Sophisticated lever design

The delicate yet robust lever blends discreetly into the background thanks to its dark colour and underlines the functional qualities of KWC ZOE. The water flow rate and temperature can be controlled with this ergonomic and pleasantly tactile lever, which moves extremely smoothly and is intuitive to use. Cold water flows when the lever is in the front position, while moving the lever into a central position (KWC ZOE lettering) produces a mixed water flow. The ideal solution for ensuring safety with children in mind.



### Smooth joins

Precise transitions and joins make the faucet particularly easy to clean.









#### With LUMINAQUA® LED technology

Lever mixer  
Lever installation only possible on the right side  
Spray covered  
up to 500 mm pull-out length  
KWC JETCLEAN  
automatic diverter reset  
integrated ON/OFF push-button with automatic  
shut-off after 30 minutes  
hose surface to fit faucet surface  
Hose guide, swivelling 270°

**10.201.122.000FL** all chrome

A 215, mains receiver

**10.201.122.127FL** decor steel

A 215, mains receiver

Scope of delivery: mains receiver 100–240 V /  
operating voltage 6.75 V / cable length 1100 mm

Flow rate normal spray 8 l/min (3 bar)

Flow rate needle spray 9 l/min (3 bar)



Lever mixer  
Lever installation only possible on the right side  
Spray covered  
up to 500 mm pull-out length  
KWC JETCLEAN  
automatic diverter reset  
hose surface to fit faucet surface  
Hose guide, swivelling 270°

**10.201.102.000FL** all chrome

A 215

**10.201.102.127FL** decor steel

A 215

Flow rate normal spray 8 l/min (3 bar)

Flow rate needle spray 9 l/min (3 bar)



Soap dispenser

**Z.536.586.000** all chrome

**Z.536.586.127** decor steel

Dimensions are given in mm. The product range, model and technical details are subject to change.



Angled water jet, please  
make sure the sink is large  
enough.




When fitting for side operation,  
ensure sufficient space from  
the wall. Wall to centre of faucet  
approx. 55 mm.



Check height of window/  
wall-mounted cupboards.



KWC AG | Hauptstrasse 57 | CH-5726 Unterkulm | Phone +41 62 768 68 68 | [www.kwc.com](http://www.kwc.com)



820630 11/13 RENZEN